



BENECOR

ODFF



BENECOR® DEF CUBE DISPENSING & STORAGE SYSTEMS

THE BENECOR® DEF CUBE OFFERS THE LATEST, MOST ADVANCED "PLUG & PLAY" DEF DISPENSING & STORAGE FOR BOTH WARM & COLD WEATHER CONDITIONS.

SAFE & EASY HANDLING

Bi-Directional Forklift Plates, Internal Baffle Plates, Galvanized Hatch Plates, Stacking Corners & Lifting Eyes To Allow Safe & Easy Handling

ECONOMICAL TRANSPORTATION

Designed To Stack Inside Shipping Containers & Across Truck Beds Providing Economical Transportation

MEETS GLOBAL ENVIRONMENTAL REGULATIONS

110% Bunded Tank Capacity - To Meet Global Environmental Regulations

EASY MAINTENANCE & CLEANING

Completely Removable Inner Stainless Steel Tank For Easy Maintenance & Cleaning

SPACE-SAVING

Easily Stack 2 High When Full & 3 High When Empty

STANDARDS / APPROVALS

UL 142, ULC S601 & USDOT

CONTAINER SPECIFICATIONS

Capacity 100G / 380L Length 4'6" / 1,375mm Width 3'4" / 1,021mm 2'8" / 822mm Height Outer Tank Thickness .118" / 3mm .15748" / 4mm Inner Tank Thickness Weight - Empty 837lb / 380kg Weight - Full 1,865lb / 845kg Safe Fluid Fill Levels 95G / 359L Stainless Steel Internal Tank

OPTIONAL CONTAINER FEATURES

250, 500 & 750 Gallon Sizes



BENECOR.COM





💓 WARM WEATHER STANDARD FEATURES

- BENECOR DEF 12 Volt Pump
- Power Connections (Gator Clips)
- 15 ft of 3/4" DEF Hose
- Automatic Nozzle
- Filter
- Dual Conservation Vent
- 2" Male Cam Coupler with Lockable Cap

WARM WEATHER KIT PART NUMBER

• 100G DEF Dispensing Kit KDD100W

※ COLD WEATHER STANDARD FEATURES

- BENECOR DEF 12 Volt Pump
- Foam Insulation 2" Tank Enclosure
- Foam Insulation 1/2" Pump Compartment
- Immersion Tank Heater 120V (1920W) or 240V (2750W)
- Strip Heater & Thermostat for Pump Compartment
- Power Panel 120V or 240V with 15' UL Electrical Cord
- 15 ft of 3/4" DEF Hose
- Automatic Nozzle
- Fill 2" Male Cam with Lockable Cap
- Filter
- Dual Conservation Vent

COLD WEATHER KIT PART NUMBERS

- 100G/120V Tank Heater DEF Dispensing Kit KDD100C-120V
- 100G/240V Tank Heater DEF Dispensing Kit KDD100C-240V

OPTIONAL FEATURES INCLUDE

20 ft of 3/4" DEF Hose (Instead of Standard 15 ft Hose)

In-line DEF Housing & Filter

Magnetic Interface Nozzle





